

[54] EXTENSIBLE HEIGHT-ADJUSTABLE SWIVEL ARM FOR SUPPORTING A DISPLAY OR THE LIKE

[75] Inventor: **Lorenz Rohr**, Augsburg, Fed. Rep. of Germany

[73] Assignee: **NCR Corporation**, Dayton, Ohio

[21] Appl. No.: **918,174**

[22] Filed: **Oct. 10, 1986**

[30] Foreign Application Priority Data

Oct. 23, 1985 [DE] Fed. Rep. of Germany 8530047

[51] Int. Cl.⁴ **E04G 3/00**

[52] U.S. Cl. **248/280.1; 248/279; 248/283; 248/289.1; 248/293**

[58] Field of Search **248/280.1, 282, 283, 248/293, 289.1, 585, 279, 106**

[56] References Cited

U.S. PATENT DOCUMENTS

1,753,875 4/1930 Baumann 248/279 X
2,994,501 8/1961 Barnard 248/279 X
3,358,957 12/1967 Lindenmuth 248/279
3,929,309 12/1975 De Vore 248/279 X

4,166,602 9/1979 Nilsen et al. 248/280.1
4,266,747 5/1981 Sounder et al. 248/280.1
4,548,373 10/1985 Komura 248/280.1 X
4,548,374 10/1985 Thompson et al. 248/280.1 X

Primary Examiner—Ramon O. Ramirez

Attorney, Agent, or Firm—Wilbert Hawk, Jr.; Casimer K. Salys

[57]

ABSTRACT

A swivel arm structure suitable for supporting a video display apparatus or the like and for positioning such apparatus with substantial discretion and ease. A first, horizontally movable arm is pivotally attached to a fixedly mounted base, which movable arm can be articulated at multiple movement interrelated joints within the horizontal plane. A vertically translating parallelogram type linkage is attached at one end to the horizontally articulatable arm and at the other end supports the apparatus. In one form one linkage member is situated within the tubelike structure of the other linkage member. The swivel arm can be freely moved, without angle induced binding of hinges, to position the apparatus.

7 Claims, 9 Drawing Figures

